

IN THE CLAIMS:

1. (Currently Amended) Sealing device (16) for a rotatably supported roll (15), ~~with the sealing device comprising~~ at least one annular body, ~~which is~~ supported on a roll neck (2), ~~encompasses and encompassing~~ said roll neck, ~~and is the annular body being~~ provided with at least one outwardly extending lip (21; 22) that rests against and seals a stationary part (7) during rotation of the roll, wherein the annular body ~~is embodied in~~ comprises at least two parts (17; 18), ~~such that wherein~~ a first part (17) rests against a part (2) of the roll (15), and a second part (18) ~~encompasses~~ comprises at least one outwardly extending lip (21; 22), and wherein the second part (18) is held in a pocket of the first part (17).
2. (Previously Presented) Sealing device in accordance with Claim 1, wherein the first part (17) and the second part (18) have different moduli of elasticity.
3. (Previously Presented) Sealing device in accordance with Claim 1, wherein the first part (17) and the second part (18) have different surface hardness values.

4. (Previously Presented) Sealing device in accordance with Claim 1, wherein the first part (17) and the second part (18) consist of different materials.
5. (Currently Amended) Sealing device in accordance with Claim 1, wherein the second part (18) ~~encompasses~~ comprises at least one lip (21) directed axially in the direction of the barrel of the roll (15) and one lip (22) directed axially in the opposite direction.
6. (Currently Amended) Sealing device in accordance with Claim [[1]] 5, wherein the lip or lips (21; 22) consist of an elastic rubber material.
7. (Currently Amended) Sealing device in accordance with Claim [[1]] 5, wherein the lip or lips (21; 22) are spring-supported.
8. (Currently Amended) Rolling device with at least one roll (15) rotatably supported in a stand and with at least one sealing device that seals the roll against a stationary area (7) of the rolling device, wherein the sealing device (16) ~~is designed in accordance with Claim 1~~ comprises at least one annular body supported on a roll neck (2) and encompassing said roll neck, the annular body being provided

with at least one outwardly extending lip (21; 22) that rests against and seals a stationary part (7) during rotation of the roll, wherein the annular body comprises at least two parts (17; 18), wherein a first part (17) rests against a part (2) of the roll (15), and a second part (18) comprises at least one outwardly extending lip (21; 22), and wherein the second part (18) is held in a pocket of the first part (17).